







































FLASHINGS

Complements

Profile	Code	Description	Weight (Kg/m)	Perimeter mm.	Inertia (cm4)
	4045	42 x 28.5 mm flashing clip	0.324	159	Ix: 1.84 Iy: 0.60
	3643	42 x 26.5 mm flashing clip	0.348	157	Ix: 1.88 Iy: 0.64
	8098	45.65 x 40.1 mm flashing clip	0.532	201	Ix: 3.71 Iy: 3.12
	4517	22.1 x 25.41 mm flashing lower register	0.221	105	Ix: 0.33 Iy: 0.42
	3591	16.9 x 26 mm flashing lower register	0.224	122	Ix: 0.15 Iy: 0.53
	3431	30.6 x 101.6 mm flashing	0.559	278	Ix: 1.05 Iy: 22.24
	3612	33 x 21 mm flashing	0.219	122	Ix: 1.08 Iy: 0.29
	3512	35 x 21.8 mm flashing	0.251	144	Ix: 1.77 Iy: 0.32
	3496	52 x 27 mm flashing	0.400	211	Ix: 4.53 Iy: 0.62
	4200	82 x 27 mm flashing	0.472	252	Ix: 14.21 Iy: 0.69
	4566	40 x 8.9 mm flashing	0.271	150	Ix: 1.65 Iy: 0.05
	4649	60 x 8.9 mm flashing	0.308	189	Ix: 4.21 Iy: 0.05
	4151	80 x 9 mm flashing	0.459	236	Ix: 11.43 Iy: 0.07
	3644	40 x 8.9 mm flashing	0.243	149	Ix: 1.47 Iy: 0.05
	3752	60 x 8.9 mm flashing	0.311	189	Ix: 3.91 Iy: 0.05
	8099	70 x 14 mm flashing	0.397	215	Ix: 5.95 Iy: 0.14

Profile	Code	Description	Weight (Kg/m)	Perimeter mm.	Inertia (cm ⁴)
	3666	31.3 x 12.3 mm flashing	0.211	119	Ix: 0.78 Iy: 0.06
	3626	31.3 x 12.3 mm flashing	0.237	134	Ix: 1.01 Iy: 0.11
	3587	28 x 17.7 mm flashing	0.238	135	Ix: 0.83 Iy: 0.16
	3704	38 x 17.7 mm flashing	0.275	154	Ix: 1.85 Iy: 0.17
	3923	38 x 22.3 mm flashing	0.286	162	Ix: 1.88 Iy: 0.34
	3588	28 x 22.3 mm flashing	0.248	138	Ix: 0.73 Iy: 0.33
	3703	38 x 22.3 mm flashing	0.292	165	Ix: 1.75 Iy: 0.35
	4027	48 x 22.3 mm flashing	0.327	185	Ix: 3.24 Iy: 0.37
	3589	28 x 20.8 mm flashing	0.251	143	Ix: 0.75 Iy: 0.37
	3702	38 x 20.8 mm flashing	0.300	170	Ix: 1.79 Iy: 0.40
	4161	65 x 51 mm flashing	0.518	258	Ix: 10.20 Iy: 4.32
	3592	42 x 26 mm flashing	0.362	193	Ix: 1.95 Iy: 0.73
	3906	42 x 26 mm flashing	0.362	187	Ix: 1.66 Iy: 0.67
	3907	42 x 26 mm flashing	0.375	201	Ix: 2.29 Iy: 0.76
	4212	89 x 26 mm flashing	0.545	292	Ix: 18.67 Iy: 0.93
	3782	60 x 26 mm flashing	0.456	241	Ix: 5.93 Iy: 0.83

Profile	Code	Description	Weight (Kg/m)	Perimeter mm.	Inertia (cm4)
	3402	83.2 x 46 mm flashing	0.651	338	Ix: 3.24 Iy: 19.82
	3781	85 x 26 mm flashing	0.542	288	Ix: 15.38 Iy: 0.92
	4112	100 x 26 mm flashing	0.605	319	Ix: 19.82 Iy: 3.24
	4518	49.6 x 19 mm flashing	0.389	206	Ix: 3.47 Iy: 0.34
	4519	64.6 x 19 mm flashing	0.446	236	Ix: 6.92 Iy: 0.37
	4520	89.6 x 19 mm flashing	0.572	305	Ix: 18.79 Iy: 0.41



Campaña s/n
36645, Valga
Pontevedra – Spain
(0034) 986 564 009
edificacion@extrugasa.com
www.extrugasa.com